



DECLARATION OF PERFORMANCE

according to Regulation (EU) No 305/2011 Annex III
(Construction Products Regulation)

For the product

codex Power CX 5

No.: 03/01/0002.01

1. Unique identification code of the product-type:

EN 12004 C2TE

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Lot-Number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Improved cementitious adhesive with reduced slip and extended open time.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

UZIN Utz AG - Dieselstrasse 3 - 89079 Ulm - Germany

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Kiwa MPA Bautest GmbH - Georg-Schumann-Str. 7 - 01187 Dresden (2007)

Has performed initial testing on 02.11.2009 according to system 3 of annex V of regulation 305/2011/EC for the marketing of construction products and has issued the test report with the following number:

DD 4437/1/2009



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	12004:2007+A1:2012
Initial tensile adhesion strength	≥ 1 N/mm ²	
Tensile adhesion strength after water immersion	≥ 1 N/mm ²	
Tensile adhesion strength after heat ageing	≥ 1 N/mm ²	
Tensile adhesion strength after freeze-thaw cycles	≥ 1 N/mm ²	
Release of dangerous substances	NPD	
Extended open time: Tensile adhesion strength	≥ 0,5 N/mm ² (30 min)	

*NPD - no performance determined

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Michael Zieger, Head of Product Safety and Compliance
(name and function)

Ulm **18.06.2013**
(place and date of issue)

Uzin Utz AG
Dieselstraße 3 | D-89079 Ulm
Postfach 4080 | D-89030 Ulm
Telefon +49 (0)731 4097-0
Telefax +49 (0)731 4097-110
Internet www.uzin-utz.com

M. Zieger
(signature)